

## MATTEI COMPRESSORS, INC. WARRANTY

Seller warrants products of its own manufacture against defects in workmanship and materials under normal use and service, as follows:



## PACKAGED AIR COMPRESSORS -

Parts and labor: Twelve (12) months from date of start-up or eighteen (18) months from date of shipment from

the factory, whichever occurs first. (Excludes consumables)

<u>Parts</u>: Three (3) years from date of shipment from the factory. (Excludes consumables)

Rotor Stator Units (RSU): Ten (10) years from date of shipment from the factory applies to Direct-Drive BLADE, ERC, AC

MAXIMA and OPTIMA Series.

Five (5) years from date of shipment from the factory for Belt-Drive BLADE Series.

OEM AIRENDS & COMPRESSORS - One (1) year from date of shipment from the Mattei; including RSU, Parts and Labor; subject to

application and ambient conditions being suitable for the compressor or airend. (Excludes

consumables)

<u>GENUINE MATTEI PARTS –</u> Sixty (60) days from date of factory shipment.

With respect to products not manufactured by Seller, Seller will, if practical, pass along the

warranty of the original manufacturer.

<u>WARRANTY TERMS</u>: The terms of coverage for the MATTEI Compressors, Inc Warranty are listed below. Failure to

follow the terms will invalidate the Revolutionary 10 Year Warranty.

START-UP & REGISTRATION: Start-up may be performed by a qualified technician. MATTEI Warranty Registration must be

performed on-line and submitted within thirty (30) days of start-up. For fast and easy warranty

registration, visit <a href="https://www.matteicomp.com/register.html">www.matteicomp.com/register.html</a>.

GENUINE PARTS AND FLUIDS: The compressor must be maintained with genuine Mattei lubricant:

Mattei Rotoroil 8000 F2 (5,000 hours maximum) Mattei Rotoroil 8000 F4 (5,000 hours maximum)

Mattei Rotoroil FG XL (4,000 hours).

## NOTE:

- 1. Maximum fluid change intervals are noted per fluid. Actual fluid change interval is to be determined by fluid sampling report, not to exceed maximum fluid change interval.
- 2. Fluid samples must be taken every 2,000 hours (1,000 hours for Rotoroil FG XL) or as directed by the analysis report.
  - a. Contact your distributor or Mattei for lubricant sampling kits. This analysis service is free from Mattei.
- 3. Only genuine MATTEI lubricants, maintenance components and replacement parts may be used on the compressor.